

Standard for Wall Thickness of Electrical Distribution Boxes



Overview

Installing safe, orderly electrical boxes and cables is made easy by following the recommended electrical codes.

Key Takeaways

Electrical distribution boxes typically have wall thicknesses of 1/16" (≈ 1.6 mm) for metal boxes and up to 1/8" (≈ 3 mm) for plastic or PVC boxes, depending on material, size, and protection rating.

Wall Thickness by Material

Metal Boxes: Standard metal electrical boxes, such as steel or aluminum, usually have walls around 1/16 inch (≈ 1.6 mm) thick. This thickness provides sufficient structural strength while maximizing internal volume for wiring and devices. Thicker walls may be used for larger enclosures or higher mechanical protection requirements.

Plastic/PVC Boxes: Plastic or PVC enclosures generally have thicker walls, ranging from 1/16 inch to 1/8 inch (≈ 1.6 – 3 mm). The increased thickness compensates for the lower rigidity of plastic and ensures durability, especially for high IP-rated or outdoor applications.

Factors Affecting Wall Thickness

- **Ingress Protection (IP) and NEMA Ratings:** Higher protection ratings (e.g., IP65, IP67, NEMA 4X) require reinforced walls, deeper doors, and thicker gaskets, which can slightly reduce internal usable space.



- **Enclosure Size:** Larger enclosures may require thicker walls or additional reinforcement to maintain rigidity and prevent deformation under load .
- **Material Strength:** Steel and aluminum allow thinner walls due to higher mechanical strength, while plastic or fiberglass-reinforced enclosures need thicker walls for equivalent durability .
- **Application Requirements:** Industrial or outdoor installations may demand thicker walls for impact resistance, fire rating, or environmental protection .

Practical Considerations

- Always verify the technical drawing for internal usable space, as wall thickness reduces the effective volume for wiring and devices .
- For retrofit or “Old Work” boxes, wall thickness may vary slightly to facilitate installation in finished walls .
- When designing or selecting a distribution box, consider future expansion, cable bending radius, and heat dissipation, which may influence the choice of wall thickness and enclosure size . In summary, while there is no single global standard, metal electrical distribution boxes commonly use 1/16" walls, and plastic boxes use up to 1/8", with adjustments based on size, material, and protection requirements. Always consult manufacturer specifications and relevant standards (NEC, IEC) for compliance and safety.

Article Content

SEC DISTRIBUTION CONSTRUCTION STANDARD

4.7 The upper edge of the cable trench shall be 50 mm wider than the standard width of the trench to form a groove of 25 x 10 mm all

Receptacle Boxes and Cable Installation Codes

Installing safe, orderly electrical boxes and cables is made easy by following the recommended electrical codes.

Distribution boards components

Service cable ducts or conduits, surface mounted or in cable chases embedded in the wall Note: to facilitate future

Contact Us

Continue your research online:

Website: <https://rivomultitrade.co.za>

Technical inquiry: <https://rivomultitrade.co.za/contact.html>

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

